

VC700

Omnidirectional Speakerphone

VC700 is a professional cascade omnidirectional microphone, able to deliver crystal clear and true-to-life sound. VC700 has perfect expansion capabilities. It is equipped with an expansion system in microphone and speaker. When users want to use it in a larger meeting room or for group discussions, the two devices can work in the same conference at the same time and the speakers and microphones of the main unit and the expansion unit are fully synchronized. Then they can be controlled with each other at the same time. That greatly optimizes the omnidirectional microphone's pickup and playback capabilities, bringing a better experience to the users.



Bluetooth 5.0



Built-in 52200mA Battery



Support Duplex Call



4-8m Voice Pick Up



Full Duplex Technology :

Featured with full duplex deep echo cancellation, 48K voice calling over broadband technology, microphone smart mix, dynamic noise reduction, and automatic gain technology.



360° Voice Pick Up :

Omnidirectional sensitive microphone can capture every tiny sound to make them more clear no matter where it is from.



High-power Speaker :

As built-in high-fidelity and high-power speakers, the voice from VC700 is continuous and undistorted.





Support Bluetooth, USB, Line IN/OUT,interface:

Support Line IN/OUT stimulate interface to connect with external communication terminal with 3.5mm audio cable. It also supports multi-media communication systems and network meeting platforms.



VC700 Omnidirectional Speakerphone

Module	Function	Description	Dimension Figure(mm)
Audio Technology Parameter	Acoustic Echo Cancellation(AEC)	Full-duplex echo cancellation depth can reach more than 65dB	 <p>152mm</p>  <p>38mm</p>
	Echo length	≥500ms	
	Two-way noise compression (NC)	Noise compression reaches 18dB	
	Smart microphone automatic direction finding technology (EMI)	Support	
	Automatic gain control (AGC)	Support	
Voice Frequency Parameter	Microphone frequency response	100HZ-22KHZ	
	Horn frequency response	100HZ-22KHZ	
	Pick up range	4M, 360°	
	Speaker volume	Maximum: 85dB	
	Speaker power	3W	
Power Supply	Built in battery	Built-in 5200mA battery , working duration is more than 8 hours. Standby time 90 days	
Main Microphone Interface	Line In/Out interface	3.5mm audio input/out interface	
	RJ45 network port	Connect to expansion microphone	
	USB	Type-B audio input/output interface	
	Power switch	Press for 3 seconds to turn off the device	
Expansion Microphone Interface	RJ45 network port	Connect to main microphone	
Others	USB	Able to connect with USB to supply power	
	Noise level	< -48 dBA	
	Support system	Windows/Andriod/iOS /Linux	
	Power supply	AC100~240V, 50-60HZ, 12W	
Accessory	Operation temperature	0°C-50°C (Operating statue)	
	Standard accessory	USB cable/cascade cable/instruction manual/certificate/warranty card	
	Optional accessory	Bluetooth Dongle	

Shenzhen Minrray Industry Co.,Ltd.

Address: 6 Floor,Building 18-A,ZhongHaiXin Technology Park,GanliRoad,Lilang Avenue,Buji,Shenzhen 518112,China
 Tel:+86-755-33288550/33288551 E-mail:market@minrrayav.com Web:www.minrrayav.com